



RTF-10 SPECIFICATIONS

Dimensions 12.5"H x 10.75"W x 6.5"D
Operating Temperature Range - 5° F to 100° F
Control Unit Enclosure NEMA-4X (with or without window)
External Hardware 3/16" Stainless Steel
Chart Panel Internal Hinged - Swing-Out
Mounting Four point flat surface
Chart Size 8" or 10" - charts available for most applications
Display 8 Digit LCD re-settable or non-re-settable
Chart Pen Movement Precision stepper motor
Input Specified by user (4 to 20 ma standard)
Rate Display 1 to 1999 counts
Hysteresis 10mv
Humidity 5 to 95% Non-condensing
Accuracy > 1 % Range
Power 120vac/60HZ -2A max

FEATURES:

Lockable

Ultrasonic Flow Meter for Weirs/Flumes/Channels (optional)

User Scalable Totalizer for use with Composite Sampler (optional)

Relays with settable controls for Tank Level control (optional)

Modular fiberglass enclosure with Flowmeter and Refrigerated

Composite Sampler for NPDES compliance (optional)

Environmental Instruments, LLC

144 Industrial Park Drive Suite A-3

Waynesville, NC 28786

Phone: 828-452-7776 Fax:828-452-7076

Website: www.theFluoroprobe.com

Email: envinst@thefluoroprobe.com